AVER VB342+ 4K VC



0.00 SAR ✓ In Stock

FEATURES :

- All-in-one 4K video sound bar
- Fit your whole team in the room with a 120° FOV
- Smart Frame captures everyone
- Smart Speaker instantly identifies speakers
- Constant clarity with True WDR

AVER VB342+ 4K VC conferencing system

Camera	Sony Exmore sensor: Ultra crystal-clear image support up to 4K Frame rate: 4K 30fps; 1080p, 720p, 960 x 540, 848 x 480, 800 x 448, 640 x 480, 640 x 360, 424 x 240, 320 x 240, 320 x 180 at 60, 30, 15fps SmartFrame & SmartSpeaker: Automatic FOV adjustment (auto focus) to fit all participants and focus on the speaker 120° wide field of view True WDR up to 120 db: Superb back light compensation technology for optimizing light balance in high-contrast conditions Digital zoom rate up to 4X leveraging 4K sensor 3D denoise technology maintains clear and natural imaging in low light conditions Mirror, AE, white balance: Auto, manual override via PTZApp Minimum focus distance: 80 cm Analytics API: Enterprises and third-party software providers can obtain people-counting data for better understanding of meeting-space usage
Motorized Pan and Tilt Movement	Pan: Total horizontal viewing area 180° Tilt: Total vertical viewing area 105° 10 camera presets (through remote control) Fast and quiet pan & tilt movement
Audio	Microphones: 2 unidirectional microphones supporting 6 m pickup 5Wx2 stereo full range speakers with professional bass port tuned for communication Volume up to 96 dB SPL at 1/2 meter Echo cancellation Noise suppression 3.5 mm Line-in (aux) cable connects BYOD smartphones or PCs as speakerphones
HDMI	DisplayLink: Built-in USB 3.1 (Gen 1) to HDMI adapter 1080p HDMI output to TV**
Connectivity	12V/5A power adaptor Mini DIN6 for RS232 connection USB type C connector HDMI out connection (DisplayLink) Phone in (3.5 mm audio jack) Mic input Wireless connection with mobile devices**
Video Format	YUV, YUY2, M-JPEG
Control	IR remote control VISCA/pelco P/pelco D via RS232 UVC/UVA plug-and-play PTZApp
Hardware Specs*	2.4 GHz Intel® Core™2 Duo processor 2 GB RAM or more USB 3.1 Gen1 port (supports 4K); USB 2.0 port (supports up to 1080p)
Power Supply	AC 100V~240V, 50/60 Hz Consumption: 12V, 5A
Dimensions	Package dimensions: 739 x 193 x 229 mm Package weight: 4.16 kg/9.3 lbs Camera: 650 x 100 x 109.5 mm/2.133 kg Remote control: 200 x 50 x 21 mm/0.09 kg
Package Contents	VB342+ unit Power cable 10 ft (3 m) USB 3.1 type-C to type-A Cable 6 ft (1.8 m) USB 3.1 type-A to type-C adapter Quick-start guide Wall-mount bracket and screws Warranty card Remote control Battery

Optional Accessories	Mini DIN6 to RS232 adapter TV mount and mounting screws 33 ft (10 m) expansion microphone 66 ft (20 m) expansion microphone 33 ft (10 m) USB 3.1 extension cable 66 ft (20 m) USB 3.1 extension cable 16 ft (5 m) USB 2.0 cable