Bosch Plena PLE-2CS 2-Zone Call Station Microphone



1,650.00 SAR ✓ In Stock

FEATURES :

Voltage Range: 24 VDC supplied by PLE mixer amplifier or mixer
Current Consumption: <30 mA
Nominal Sensitivity: 85 dB SPL (gain preset 0 dB)
Nominal Output Level: 700 mV
Maximum Input Sound Level: 110 dB SPL
Gain Preset: +6 / 0 / -15 dB

Bosch Plena PLE-2CS 2-Zone Call Station Microphone	
Sensitivity	85dB SPL (Gain Preset 0dB)
Nominal Output Level	700mV
Max Input Sound Level (SPL)	110dB SPL
Frequency Response	100Hz – 16kHz
Output Impedance	200 Ohms
Connectors	2 x RJ45 Connectors
Cable Length	16.4′ (5 m)
Power	24VDC
Current Consumption	< 30mA
Environmental Operating Temp:	14 to 131°F (-10 to 55°C) Storage Temp: -40 to 158°F (-40 to 70°C) Relative Humidity: < 95%
Dimensions	Base: 1.57 x 3.97 x 9.25″ (40 x 100 x 235mm) (HxWxD) Stem Length: 15.35″ (390mm) (With Mic)
Weight	2.2 lbs (1kg)