Dynacord CMS 600-3 Compact 8-Channel Mixer



8,400.00 SAR ✓ In Stock

FEATURES :

- Dimensions (W x H x D), mm
- 416.9 x 109.6 x 347.8
- Optional Accessories
- RMK-600-3 (Rack Mount Kit for CMS 600-3

Dynacord CMS 600-3 Compact 8-Channel Mixer

Channels	4 x Mic/Line 2 x Mic/Stereo Line 2 x Stereo Line
Auxiliary	1 x Pre (MON) 1 x Pre/Post Switchable (AUX)
Gain	Microphone (Line -20 dB): 10 to 60 dB Trim Line/CD (Stereo): -10 to 20 dB
Maximum	THD @ 1kHz Microphone Input to Master A L/R Outputs, +16 dBu, Typical: < 0.005% Frequency Response, -3 dB, ref. 1 kHz, any input to any Mixer Output: 15 Hz to 70 kHz
Crosstalk @ 1 kHz	Fader and FX/AUX/MON-Send Attenuation: > 85 dB Channel-to-Channel: < -80 dB Mute and Standby Switch Attenuation: > 100 dB CMRR, Microphone Input:> 80 dB Input Sensitivity (All Level Controls in Max. Position Microphone / Line, Mono / Line, Stereo / CD, Stereo): -74 dBu (155 µV) / -54 dBu (1.55 mV) / -34 dBu (15.5 mV) / -34 dBu (15.5 mV)
Equalization	LO Shelving: ± 15 dB / 60 Hz MID Peaking: ± 12 dB / 2.4 kHz HI Shelving: ± 15 dB / 12 kHz Master EQ 9-Band (63, 125, 250, 500, 1 kHz, 2 kHz, 4 kHz, 6.3 kHz, 12 kHz): ± 10 dB / Q = 1.5 to 2.5
Power Consumption	At 1/8 Maximum Output Power, 4 Ohms: 35 W
Digital Audio	Channels: 4 Inputs / 4 Outputs AD/DA Conversion, Sampling Rate 24-Bit, 44.1 / 48 / 88.2 / 96 kHz PC Interface: USB 2.0, Female Type-B MIDI Interface: 5-Pin DIN Connector, Input / Output
Ambient Temperature	40 to 105°F / 5 to 40°C
Dimensions	16.4 x 4.3 x 13.7" / 416.9 x 108.6 x 347.8 mm Rackmount (7.5 HE): 19 x 3.9 x 13.1" / 483 x 99.1 x 332.6 mm
Weight	12.8 lb / 5.8 kg