ITC T-2S500 RMS 2×500W Two Channel Power Amplifier, 100V/70V/4ohms



0.00 SAR ✓ In Stock

FEATURES :

- 2 separate amplifier into one chassis
- Rack mount amplifier in 2U (T-2S60/T-2S120) and 3U (T-2S240/T-2S350/T-2S500) types
- Rated power from 60W, 120W, 240W, 350W to 500W per channel
- 70V, 100V and 4-16ohm speaker outputs for each channel
- Isolated transformer for human safety operation

ITC T-2S500 RMS 2×500W Two Channel Power Amplifier

Brand & Model	ITC T-2S500
Product Category	2-Channel High-Impedance Power Amplifier
Rated Power Output	2 × 500W RMS (1000 Watts total continuous load)
Distributed Line Output	Constant Voltage 70V and 100V terminal connections
Input Sensitivity / Impedance	775mV / 10KΩ
Frequency Response	50 Hz to 16,000 Hz (±3dB)
Signal-to-Noise (S/N) Ratio	Better than 90dB
Rack Height Profile	Standard 3U Height Profile (19-inch rack-ready chassis)
Power Requirements	AC ~220V–240V, 50/60Hz
Dimensions (W × D × H)	484 × 458 × 132 mm
Net Unit Weight	Approx. 25.8 kg