ITC T-4S240 RMS 4×240W Four Channel Power Amplifier, 100V/70V/4ohms



0.00 SAR ✓ In Stock

FEATURES :

- 4 separate amplifier into one chassis
- Rack mount amplifier in 2U(T-4S60/T-4S120) and 3U(T-4S240) types
- Rated power from 60W, 120W to 240W per channel
- 70V, 100V and 4-16ohm speaker outputs for each channel by phoenix types
- Isolated transformer for human safety operation

ITC T-4S240 RMS 4×240W Four Channel Power Amplifier

Brand & Model	ITC T-4S240
Product Category	4-Channel High-Impedance Power Amplifier
Rated Power Output	4 × 240W RMS (960 Watts total structural load capacity)
Circuit Design	4 completely distinct and isolated amplifier channels in one frame
Output Impedance Loads	4Ω to 16Ω (Ohms) direct low-impedance terminals
Distributed Output Lines	Constant Voltage 70V and 100V terminal connections
Total Harmonic Distortion	≤ 1% at 1KHz (rated power capacity)
Frequency Response	50 Hz to 16,000 Hz (±3dB limits)
LED Status Elements	Power (Blue/Green), Signal (Green), Peak (Red), and Protection (Amber)
Power Input Grid	AC ~220V–240V 50/60Hz mains line supply