TOA A-2030 Mixer Power Amplifier High-Quality Sound



780.00 SAR ✓ In Stock

FEATURES :

- High-Quality Sound
- Watt: 30W
- FREQUENCY: 50 – 20,000 Hz
- MIC Port: 03, AUX: 02
- Priority Paging

TOA A-2030 Mixer Power Amplifier High-Quality Sound

Power Source	220 – 240 V AC, or 24 V DC
Rated Output	30 W
Power Consumption	34 W (EN60065), 2 A (DC operation at rated output)
Frequency Response	50 – 20,000 Hz (±3 dB)
Distortion	1% or less at 1 kHz, 1/3 rated power
Input	MIC 1 – 3: -60 dB*, 600 Ω, balanced, equivalent to XLR-3-31 type AUX 1, 2: -20 dB*, 10 kΩ, unbalanced, RCA pin jack Mute: Contact screw terminal (for MIC 1)
Output	Speaker out: Balanced (floating), M3.5 screw terminal, distance between barriers: 8.3 mm (0.33″) High impedance: 330 Ω (100 V), 170 Ω (70 V) Low impedance: 4 Ω (11 V) Rec out: 0 dB*, 600 Ω, unbalanced, RCA pin jack
Phantom Power	DC +21 V (MIC 1)
Tone Control	Bass: ±10 dB at 100 Hz Treble: ±10 dB at 10 kHz
Dimensions	420 (W) × 100.9 (H) × 280.3 (D) mm (16.54″ × 3.97″ × 11.04″)
Weight	5 kg (11.05 lb)