



0.00 SAR ✓ In Stock

FEATURES :

Model: A-3524D

Power Source: 100 - 240 V

Rated Output: 240 W

Frequency: 50 Hz - 20 kHz

S/N Ratio: 88 dB

+966 530651576 | www.unityservicesksa.com

TOA A-3524D Digital Mixer Amplifier

Power Source	100 - 240 V AC, 50/60Hz
Rated Output	240 W
Power/Current Consumption	314 W (Rated output), 70 W (based on EN62368), 200 mA or less (when power switch is OFF)
Frequency Response	50 Hz - 20 kHz ± 3 dB (1/8 rated output)
Distortion	1 % or less at 1 kHz, rated power (20 kHz LPF (AUX-0025))
Tone Control	Bass: ± 10 dB at 100 Hz Treble: ± 10 dB at 10 kHz
S/N Ratio	88 dB or more (Master volume: min.) 76 dB or more (Master volume: max.) 55 dB or more (INPUT 1 - 6) 72 dB or more (INPUT 7) (A-weighted)
Audio Input	INPUT 1, 2: -60 dB(*1)(MIC) / -20 dB (*1) (LINE) selectable, 600 Ω , electronically-balanced, removable terminal block (5 pins)/ $\varnothing$ 6.3 mm phone jack (3P) Note: MIC inputs are equipped with phantom power (24V DC, ON/OFF switchable) INPUT 3: -60 dB(*1), 600 Ω , electronically-balanced, $\varnothing$ 6.3 mm phone jack (3P) INPUT 4: -60 dB(*1)(MIC) / -20 dB (*1) (LINE) selectable, 600 Ω , electronically-balanced, $\varnothing$ 6.3 mm phone jack (3P) INPUT 5: -20 dB (*1), 10 k Ω , unbalanced, RCA pin jack x 2 PWR AMP IN: 0 dB (*1), 600 Ω , unbalanced, RCA pin jack
Audio Output	Speaker out: Low impedance (4 - 16 Ω) / High impedance (DIRECT, ZONE 1, ZONE 2: 100 V / total 42 Ω), removable terminal block (6 pins) (ZONE 1 / ZONE 2 is selectable, max. 240 W per output) Rec out: 0 dB(*1), 600 Ω , unbalanced, RCA pin jack Line out 1, 2: 0 dB (*1) , 600 Ω , unbalanced, RCA pin jack (Interlock with zone selection is possible)
Control Input	2 channels. no-voltage make contact input, open voltage: 35 V DC or less, Short circuit current: 10 mA or less, removable terminal block (5 pins) ZONE CONTROL IN: No-voltage make contact input, even voltage: 35 V DC or less, short-circuit current: 10 mA or less, removable terminal block (4 pins)
Control Output	POWER REMOTE OUT: Open collector output, withstand voltage: 30 V DC or less, control current: 25 mA or less, removable terminal block (4 pins) EMERGENCY OUT: Open collector output, withstand voltage 30 V DC or less, control current: 25 mA or less, removable terminal block (4 pins) ZONE CONROL OUT: Open collector output (polarized), withstand voltage 30 V DC or less, control current: 25 mA or less, removable terminal block (4 pins)

Operating Temperature	-10°C to +40°C
Dimensions	420 (W) × 96.1 (H) × 313.1 (D) mm
Weight	4.9 kg
Accessory	Power Cord (2 m) x 1, Audio Input Removavble Terminal Plug (3.81 mm, 5 pins) x 2, Control I/O Removable Terminal Plug (3.81 mm, 4 pins) x 2, Remote Control Removable Terminal Plug (3.5 mm, 4 pins) x 1, Speaker Out Removable Terminal Plug (5 mm, 6 pins) x 1, Volume Control Cover x 4