



0.00 SAR ✓ In Stock

FEATURES :

Model: A-5012

Power Source: 100-240V

Rated Output: 120 W

Frequency: 50 Hz - 20 kHz

Dimensions: 210 (W) × 52.5

+966 530651576 | www.unityservicesksa.com

TOA A-5012 Half-Rack Amplifier

Power Source	100-240 V AC, 50/60 Hz
Rated Output	120 W
Power/CurrentConsumption	207 W (rated output), 39 W (based on cULus standards) Max. 3 A
Frequency Response	50 Hz - 20 kHz (1/8 rated output)
Distortion	1 % or less (1 kHz, rated output)
Input	INPUT 1, 2: MIC -60 dB(*1) LINE -20 dB(*1) MIC/LINE selectable 2.2 kΩ, electronically-balanced, removable terminal block (5 pins) INPUT 3, 4: LINE -20 dB(*1), 10 kΩ, unbalanced, RCA pin jack
Output	SPEAKER: 4 Ω, 70 V (42 Ω), 100 V (83 Ω), removable terminal block (5 pins)
Signal to Noise Ratio	MIC 1, 2: 50 dB or more LINE 1 - 4: 70 dB or more (A-weighted)
Function	Parametric equalizer: 5 points settable on each input and output 20 Hz - 20 kHz ±15 dB Q: 0.267 - 69.249 Compressor: ON/OFF settable on Inputs 1 and 2 (OFF by default) Threshold, Ratio, Attack time, Release time, and Gain are settable independently on each input.
Network I/F	100BASE-TX
Operating Temperature	0 °C to +40 °C (32 °F to 104 °F)
Operating Humidity	35 % to 80 %RH (no condensation)
Dimensions	210 (W) × 52.5 (H) × 375 (D) mm (8.27 × 2.07" × 14.76")
Weight	3.9 kg (8.6 lb)