TOA AT-303AP Attenuator



0.00 SAR ✓ In Stock

FEATURES :

The AT-303AP is a flush-mounted wall attenuator and uses a transformer which allows connectionof a wide range of loads (30 W or less). Volume can be adjusted in five steps. The AT-303AP features push-in terminal block for easy connection

• Attenuators with 5 step attenuation: „OFF“ -18 dB, -12 dB, -6 dB, 0 dB
• Push-in connector allows quick terminalcableconnection
• Knob, panel, plate: ABS resin, white (RAL 1013 or equivalent), case: ABS resin, black
• 30 W

TOA AT-303AP Attenuator	
Input Range	0.5 W - 30 W
Attenuation	5 steps (0 dB, -6 dB, -12 dB, -18 dB, OFF)
Applicable Cable	600 V vinyl-insulated cable (Indoor Vinyl or Heat-resistant Indoor Vinyl cable) Solid cable: φ0.8 (0.03") - φ1.6 (0.06") mm
Operating Temperature	-10 ℃ to +50 ℃
Dimensions	70 (W) × 120 (H) × 52.4 (D) mm (2.76" × 4.72" × 2.06") (with plate) 41 (W) × 108 (H) × 52.4 (D) mm (1.61" × 4.25" × 2.06") (attenuator only)
Weight	210 g (0.46 lb) (unit only)
Accessory	Plate ...1, Plate mounting screw ...2, Box mounting screw ...2