



0.00 SAR ✓ In Stock

FEATURES

The BS-1030B is a small 2-way bass-reflex type speaker featuring a wide frequency range suitable for use for announcements and music playback. The BS-1030B can be used for both high impedance and low impedance applications. The speaker's splash-proof construction permits it to be installed under the eaves where the speaker is not directly exposed to rain.

+966 530651576 | www.unityservicesksa.com

TOA BS-1030B Universal Speaker

ENCLOSURE	2-way bass-reflex type
RATED INPUT	30 W
RATED IMPEDANCE	8 Ω 100 V line: 330 Ω (30 W), 500 Ω (20 W), 670 Ω (15 W), 1 kΩ (10 W), 2 kΩ (5 W) 70 V line: 170 Ω (30 W), 250 Ω (20 W), 330 Ω (15 W), 500 Ω (10 W), 1 kΩ (5 W)
SOUND PRESSURE LEVEL	90 dB (1 W, 1 m)
FREQUENCY RESPONSE	80 Hz - 20 kHz
SPEAKER COMPONENT	12 cm cone-type + dome-type
SPEAKER CORD	2-core cabtyre cord with diameter of 6 mm
OPERATING TEMPERATURE	-10 °C to +50 °C
FINISH	Enclosure: ABS resin, black (RAL9011 GRAPHITE BLACK), paint Net: Surface treated steel plate, black (RAL9011 GRAPHITE BLACK), powder coating Bracket: Surface treated steel plate, black equivalent to RAL9011 GRAPHITE BLACK, powder coating
DIMENSION	196 (W) × 290 (H) × 150 (D) mm (unit only)
WEIGHT	2.5 kg (unit only)