TOA BS-1030W Universal Speaker



0.00 SAR ✓ In Stock

FEATURES :

2-way bass reflex speaker
PA box speaker
Various installation options
high impedance (100V)
Compliance with IPX4

TOA BS-1030W Universal Speaker	
ENCLOSURE	2-way bass-reflex type
RATED INPUT	30 W
RATED IMPEDANCE	8 Ω 100 V line: 330 Ω (30 W), 500 Ω (20 W), 670 Ω (15 W), 1 kΩ (10 W), 2 kΩ (5 W) 70 V line: 170 Ω (30 W), 250 Ω (20 W), 330 Ω (15 W), 500 Ω (10 W), 1 kΩ (5 W)
SOUND PRESSURE LEVEL	90 dB (1 W, 1 m)
FREQUENCY RESPONSE	80 Hz – 20 kHz
SPEAKER COMPONENT	12 cm cone-type + dome-type
OPERATING TEMPERATURE	-10 ℃ to +50 ℃
FINISH	Enclosure: ABS resin, white (RAL9010 PURE WHITE), paint Net: Surface-treated steel plate, white (RAL9010 PURE WHITE), powder coating Bracket: Surface-treated steel plate, white equivalent to RAL9010 PURE WHITE, powder coating
DIMENSION	196 (W) × 290 (H) × 150 (D) mm (unit only)
WEIGHT	2.5 kg (unit only)