TOA BS-1034 10Watt Wall Speaker High Quality



350.00 SAR ✓ In Stock

FEATURES :

- 2-way speaker
- Easy and quick installation
- Attractive design based on the golden ratio
- Input impedance selector with rotary switch
- Fire resistant according to UL 94-V0

TOA BS-1034 10Watt Wall Speaker

RATED INPUT	10 W
RATED IMPEDANCE	100 V line: 1 kΩ (10 W), 2 kΩ (5 W), 3.3 kΩ (3 W), 10 kΩ (1 W) 70 V line: 500 Ω (10 W), 1 kΩ (5 W), 2 kΩ (2.5 W), 3.3 kΩ (1.5 W), 10 kΩ (0.5 W)
SENSITIVITY	90 dB (1 W, 1 m)
FREQUENCY RESPONSE	120 – 20,000 Hz
SPEAKER COMPONENT	Low frequency: 12 cm (5″) cone-type, High frequency: Balanced dome-type
INPUT CONNECTOR	M4 screw terminal, distance between barriers: 11 mm (0.43″)
FINISH	Enclosure: HIPS resin (fire resistant grade UL94 V-0 or its equivalent), off-white (RAL 9010 or equivalent color) Net: Steel plate, off-white (RAL 9010 or equivalent color), paint
DIMENSIONS	210 (W) × 330 (H) × 80 (D) mm (8.27″ × 12.99″ × 3.15″)
WEIGHT	1.4 kg (3.09 lb)