# TOA BS-633A Wall Mount Speaker




**0.00 SAR** ✓ In Stock

**FEATURES :**

use in BGM and announce
Compact design
Quick and easy installation
High cost-effectiveness
Built-in attenuator

| TOA BS-633A Wall Mount Speaker | |
|---|---|
| Rated Input | 6 W (100 V line), 3 W (70 V line) |
| Rated Impedance | 100 V line: 1.7 kΩ (6 W), 3.3 kΩ (3 W), 10 kΩ (1 W) 70 V line: 1.7 kΩ (3 W), 3.3 kΩ (1.5 W), 10 kΩ (0.5 W) |
| Sensitivity | 91 dB (1 W, 1 m) |
| Frequency Response | 120 - 15,000 Hz (-20 dB) |
| Speaker Component | 12 cm (5) cone-type" |
| Applicable Cable | 600 V vinyl-insulated cable (IV wire or HIV wire) Solid copper wire: φ0.8 - φ1.6 mm (equivalent to AWG 20 - 14) 7-core twisted copper wire: 0.75 - 1.25 m□ (equivalent to AWG 18 - 16) |
| Operating Temperature | -10℃ to +50℃ (14□F to 122□F) |
| Dimensions | 173 (W) × 195 (H) × 101 (D) mm (6.81 × 7.68" × 3.98")" |
| Weight | 780 g (1.72 lb) |
| Accessory | Speaker mounting screw (4 × 35 (0.16 × 1.38")) ... 2 Speaker mounting screw (4 x 16 (0.16 x 0.63")) ... 2 |