



660.00 SAR ✓ In Stock

FEATURES :

- use in BGM and announce
- Compact design
- Quick and easy installation
- High cost-effectiveness
- Built-in attenuator

+966 530651576 | www.unityservicesksa.com

TOA BS-633AT Wall Mount Speaker

RATED INPUT	6 W (100 V line), 3 W (70 V line)
RATED IMPEDANCE	100 V line: 1.7 kΩ (6 W), 3.3 kΩ (3 W) 70 V line: 1.7 kΩ (3 W), 3.3 kΩ (1.5 W)
SENSITIVITY	91 dB (1 W, 1 m)
FREQUENCY RESPONSE	120 – 15,000 Hz (-20 dB)
SPEAKER COMPONENT	12 cm (5") cone-type
APPLICABLE CABLE	600 V vinyl-insulated cable (IV wire or HIV wire) Solid copper wire: $\phi 0.8 - \phi 1.6$ mm (equivalent to AWG 20 – 14) 7-core twisted copper wire: 0.75 – 1.25 mm ² (equivalent to AWG 18 – 16)
ATTENUATION LEVEL	3 W: OFF, 1 (-12 dB), 2 (-6 dB), 3 (0 dB) 6 W: OFF, 1 (-13 dB), 2 (-7 dB), 3 (0 dB)
OPERATING TEMPERATURE	-10°C to +50°C (14°F to 122°F)
DIMENSIONS	173 (W) × 195 (H) × 101 (D) mm (6.81" × 7.68" × 3.98") (excluding volume control)
WEIGHT	810 g (1.79 lb)