



0.00 SAR ✓ In Stock

FEATURES :

- Type: Powered Box Speaker
- Frequency Response: 60 Hz - 18 kHz
- Power Output: 30W RMS
- Dimensions: 310 mm x 430 mm x 215 mm



+966 530651576



www.unityservicesksa.com

TOA BS-P1030W Powered Box Speaker

Enclosure	2-way bass-reflex type
Power Source	24 V DC, 1.5 A (DC Socket "+" Type A: 5.5 x 2.1mm)
Power Consumption	24 W (1A) at rated output
Input	5 kΩ, unbalanced (RCA plug) Maximum input: +6 dB V (2 Vrms)
Signal Gain	+30 dB
Sound Pressure Level	90 dB (1 W, 1 m)
Frequency Response	80 Hz - 20 kHz
Speaker Cord Length:	2m Flying Lead (RCA plug) & DC socket ("+")
Finish	Enclosure: ABS resin, white (RAL9010 PURE WHITE), paint Net: Surface treated steel plate, white (RAL9010 PURE WHITE), powder coating Bracket: Surface treated steel plate, white equivalent to RAL9010 PURE WHITE, powder coating
Dimension	196 (W) × 290 (H) × 150 (D) mm (unit only)
Weight	2.5 kg (unit only)