



0.00 SAR ✓ In Stock

FEATURES

The CM-760 speaker allows selection of most suitable front panel out of the CP-70 series panels (optional) depending on the installation place. Thanks to its coil spring catch method, the panel can be easily attached to the speaker. The CM-760 comes with a push-in connector which permits instant wire connection for bridging and branch wiring. The speaker is protected by a hard speaker cover.

+966 530651576 | www.unityservicesksa.com

TOA CM-760 Separate Type Ceiling Speaker

Rated Input	6 W
Rated Impedance	1.7 kΩ (6 W), 3.3 kΩ (3 W), (6.7 kΩ (1.5 W), 13 kΩ (0.8 W): Internal wiring must be changed)
Sound Pressure Level	90 dB (1 W, 1 m)
Frequency Response	100 - 16,000 Hz
Speaker Component	12 cm dynamic cone-type speaker
Dimensions for Fixing Hole	φ150 (mounting hole) × 50 (ceiling thickness) mm
Applicable Cables	600 V Vinyl-insulated cable (IV wire or HIV wire) Solid copper wire: φ0.8 - φ1.2 mm 7-core twisted copper wire: 0.75 - 1.25 mm ²
Connection	Push-in connector (Bridging and branch connections possible.)
Finish	Grille: Fire-resistant, high-impact styrene resin (resin material grade: UL94 V-O or its equivalent), black
Dimensions	215 (W) × 134 (H) × 89 (D) mm
Weight	630 g
Applicable Panel	CP-70 series panel (option): CP-73, CP-77