TOA DA-250D 2-Channel Digital Power Amplifier



0.00 SAR ✓ In Stock

FEATURES :

Model: DA-250D
Power Source: 220 - 240V
Rated Output: 250 W×2(4 Ω)
S/N Ratio: 100 dB
Weight: 5.3 kg

TOA DA-250D 2-Channel Digital Power Amplifier	
Power Source	220 - 240 V AC, 50/60 Hz
Amplification System	Class D
Power Consumption	150 W (based on EN standards) 620 W (rated output 4 Ω × 2) 400 W (rated output 8 Ω × 2)
Input	2 circuits, +4 dB* (1.23V) (input level control in max. position), 10 kΩ, electronically-balanced, removable terminal block (3 pins), XLR-3-31 type connector CH 1 mode ON/OFF switch (ON: PARALLEL, OFF: STEREO)
Rated Output	2 channels: 250 W × 2 (4 Ω), 170W x 2 (8 Ω) 1 channel (BRIDGE): 500 W × 1 (8 Ω) M4 screw terminal, distance between barriers: 8.8 mm (0.35")
Frequency Response	20 Hz - 20 kHz (±1 dB)
Total Harmonic Distortion	0.1 % (1 kHz) 0.3 % (20 Hz - 20 kHz)
Protection Circuit	Protection against excessive current flow due to overload short circuit, unusual DC voltage output, temperature rise at power amp. heat sink (100 °C (212 °F) or more) temperature rise inside the unit (80 °C (176 °F) or more)
S/N Ratio	100 dB (A-weighted)
Crosstalk	70 dB (A-weighted)
LED Indicator	Power (blue) × 1, Input (green) x 2, Output (yellow) x 2, Peak (red) x 2, Protect (red) × 2
Operating Temperature	-10 °C to +40 °C (14 °F to 104 °F)
Dimensions	482 (W) × 44 (H) × 401.8 (D) mm (18.98 × 1.73" × 15.82)
Weight	5.3 kg (11.68 lb)
Accessory	Power cord (2 m (6.56 ft)) x 1, Removable terminal plug (3 pins) x 2, Tamper-proof cap x 2, Rack mounting screw (with plain washer) x 4