



TOA DA-250FH 4-Channel Digital Power Amplifier -1000W (4 x 250W) 70V/100V High-Impedance PA Amp



0.00 SAR ✓ In Stock

FEATURES :

Model: DA-250FH

Power Source: 220 - 240V

Rated Output: 250 W x 4

Frequency: 50 Hz - 20 kHz

Weight: 6.8 kg

+966 530651576 | www.unityservicesksa.com

TOA DA-250FH 4-Channel Digital Power Amplifier

Power Source	220 - 240 V AC, 50/60 Hz
Power Consumption	294 W (based on EN standards) 1150 W (rated output 100 V line, 40 Ω x 4)
Input	4 circuits, +4 dB* (1.23V) (input level control in max. position), 10 k Ω , electronically-balanced, removable terminal block (3 pins), CH 1 mode ON/OFF switch (ON: CH 1 to All ch, OFF: Each ch)
Rated Output 0.35")	4 channels: 250 W x 4 (100 V line, 40 Ω) M4 screw terminal, distance between barriers: 8.8 mm (
Frequency Response	50 Hz - 20 kHz (-3 dB, +1 dB)
Total Harmonic Distortion	0.1 % (1 kHz) 0.3 % (100 Hz - 20 kHz)
Protection Circuit	Protection against excessive current flow due to overload short circuit, unusual DC voltage output, temperature rise at power amp. heat sink (100 °C (212 °F) or more) temperature rise inside the unit (80 °C (176 °F) or more)
S/N Ratio	100 dB (A-weighted)
LED Indicator	Power (blue) x 1, Input (green) x 4, Output (yellow) x 4, Peak (red) x 4, Protect (red) x 4
Operating Temperature	-10 °C to +40 °C (14 °F to 104 °F)
Dimensions	482 (W) x 44 (H) x 401.8 (D) mm (18.98 x 1.73" x 15.82)
Weight	6.8 kg (14.99 lb)