Toa F-1000BT Wide-dispersion Speaker System High Quality



500.00 SAR ✓ In Stock

FEATURES :

- Low and high-impedance
- Up to 90-Watt
- 2-way speaker
- Dispersion angle of 90° x 90°
- Pan-tilt wall/ceiling bracket

Toa F-1000BT Wide-dispersion Speaker System

RATED INPUT	15 W (high impedance)
POWER HANDLING CAPACITY	Continuous pink noise: 30 W (low impedance) Continuous program: 90 W (low impedance)
RATED IMPEDANCE	8 Ω 100 V line: 670 Ω (15 W), 2 kΩ (5 W), 3.3 kΩ (3 W), 10 kΩ (1 W) 70 V line: 330 Ω (15 W), 670 Ω (7.5 W), 2 kΩ (2.5 W), 3.3 kΩ (1.5 W), 10 kΩ (0.5 W)
SENSITIVITY	87 dB (1 W, 1 m) at installation in 1/2 free sound field
FREQUENCY RESPONSE	85 Hz – 20 kHz, -10 dB at installation in 1/2 free sound field
CROSSOVER FREQUENCY	5 kHz
DIRECTIVITY ANGLE	Horizontal: 90□, Vertical: 90□
SPEAKER COMPONENT	Low frequency: 10 cm (4″) cone-type High frequency: Balanced dome tweeter
FINISH	Enclosure: HIPS, black Punched net: Surface-treated steel plate, black, paint Joint bracket, wall bracket: Steel plate, t1.6, black, paint Speaker bracket: Die-cast aluminum, black, paint
DIMENSIONS	130 (W) × 202 (H) × 131 (D) mm (5.12″ × 7.95″ × 5.16″)
WEIGHT	2 kg (4.41 lb) (including the supplied brackets)
ACCESSORY	Speaker bracket…1, Joint bracket…1, Wall bracket…1, Bracket fixing screw…1 set