TOA F-1300BT 30-Watts Wide-dispersion Speaker System



750.00 SAR ✗ Out of Stock

FEATURES :

- Compact wide-dispersion
- 150 W continuous program
- Dispersion angle of 110° x 100°
- 2-way speaker
- Pan-tilt wall/ceiling bracket

TOA F-1300WT Wide-dispersion Speaker System

RATED INPUT	30 W (high impedance)
POWER HANDLING CAPACITY	Continuous pink noise: 50 W (low impedance) Continuous program: 150 W (low impedance)
RATED IMPEDANCE	8 Ω 100 V line: 330 Ω (30 W), 1 kΩ (10 W), 3.3 kΩ (3 W), 10 kΩ (1 W) 70 V line: 170 Ω (30 W), 330 Ω (15 W), 1 kΩ (5 W), 3.3 kΩ (1.5 W), 10 kΩ (0.5 W)
SENSITIVITY	90 dB (1 W, 1 m) at installation in 1/2 free sound field
FREQUENCY RESPONSE	80 Hz – 20 kHz, -10 dB at installation in 1/2 free sound field
CROSSOVER FREQUENCY	2 kHz
DIRECTIVITY ANGLE	Horizontal: 110□, Vertical: 100□
SPEAKER COMPONENT	Low frequency: 13 cm (5″) cone-type High frequency: 25 mm (1″) dome tweeter
INPUT TERMINAL	Push-in terminal
FINISH	Enclosure: HIPS, white Punched net: Surface-treated steel plate, white, paint Joint bracket, wall bracket: Steel plate, t1.6, white, paint Speaker bracket: Die-cast aluminum, white, paint
DIMENSIONS	162 (W) × 250 (H) × 161 (D) mm (6.38″ × 9.84″ × 6.34″)
WEIGHT	3.6 kg (7.94 lb) (including the supplied brackets)