TOA FV-200EV Emergency Message Panel – Automated Voice Evacuation Controller



0.00 SAR ✓ In Stock

FEATURES :

The FV-200EV Emergency Message Panel is the emergency broadcast operating section of the FV-200 Series Emergency Public Address System. It need not be installed when the system is used solely for general broadcasting purpose. It has facilities to manually start and reset emergency broadcasts. Emergency announcements are recorded in English (default settings), which can be changed by USB data transfer operations from rear panel.

TOA FV-200EV Emergency Message Panel

Power Source	Usable Power Supply Unit: FV-200PS 24 V DC (operating range: 19.5 - 27 V), M3 screw terminal
Current Consumption	250 mA
Audio Input	Fireman's microphone: -55 dB*, 600 Ω, unbalanced, XLR-3P connector
Audio Output	EV : -20 dB*, unbalanced, Removable terminal block (2 pins)
Control Input	FA Input : No-voltage make contact input, Open voltage : 24 V DC, Short-circuit current: Under 5 mA, Removable terminal block (2pins)
Control Output	Control output : Relay contact output x 4, rated voltage : 24 V DC,R emovable terminal block (2 pins)
Frequency Response	20 Hz - 20 kHz, ±3 dB, 1 kHz
LED Indicator	Power (Green), Fire (Red), Alert announcement (Green), Evacuation announcement (Green), False announcement (Green), Clear announcement (Green), USB (Green)
Operating Temperature	0 ℃ to +40 ℃
Operating Humidity	Under 90% RH (no condensation)
Finish	Front Panel : Aluminum, black, alumite
Dimensions	482 (W) × 100 (H) × 396.7 (D) mm
Weight	4.3 kg (with microphone)
Accessory	Removable terminal plug (2 pins) x 7, Fireman's Microphone x 1, Instruction Manual x 1