TOA FV-200RF Remote Microphone Receiver – 4-Channel Input Module for TOA RM-200M Paging Stations



0.00 SAR ✓ In Stock

FEATURES :

Model : EV-200M
Operating Humidity : Under 90% RH
Dimensions : 482 (W) × 44 (H) × 320 (D) mm
Weight: 2.8 kg
Power Source : 24 V DC,

TOA FV-200RF Remote Microphone Receiver

Power Source	Usable Power Supply Unit: FV-200PS 24 V DC (operating range: 19.5 - 27 V), M3 screw terminal
Current Consumption	230 mA
No. of Zone Groups in Speaker Selector	Max. 10 (SS-2010, SS-1010R, SS-1010)
Control Input	All call :1 input,No-voltage make contact input,open voltage 24V DC, short-circuit current : Under 5 mA, removable terminal block (2 pins)
Control Output	SS Control : 55 outputs, open collector output, removable terminal block (6 pins)
Usable Remote Microphone	RM-200M Remote microphone extention unit : RM-210 (Max. 4 units)
No. of Connectable to Remote Microphone	Max. 4 x RM-200M
S/N Ratio	Over 60 dB
Operating Temperature	0 ℃ to +40 ℃
Operating Humidity	Under 90% RH (no condensation)
Dimensions	482 (W) × 44 (H) × 320 (D) mm
Weight	2.8 kg
Accessory	Removable terminal plug (2 pins) x 2, removable terminal plug (3 pins) x 1, removable terminal plug (6 pins) x 10, Instruction Manual x 1