TOA FV-2148W Integrated PA/VA System



0.00 SAR ✓ In Stock

FEATURES :

FV-2148W is a compact and lightweight Voice Evacuation wall mount system. It is designed for both general and emergency purpose broadcasts. The wall mount system is comprised of the 4 pre-recorded Voice Evacuation messages, 480 W digital power amplifier modules, 10 speaker zone selector, and is able to connect up to 4 remote microphones.
The FV-2148W can link with the fire alarm panel. Emergency messages are automatically broadcast when the fire alarm is activated.

TOA FV-2148W Integrated PA/VA System	
Model	FV-2148W
Power Source	100 - 240 V AC ~ 50/60 Hz, M4 screw terminal
Power Consumption	99 W (EN 62368-1) 530 W (Rated Output)
Rated Output	480 W
Input	Front Microphone: -60 dB*, 2.2 KΩ, unbalanced, XLR connector Input 1: -60 dB*/-20dB* (selectable), 2.2 KΩ, balanced, screw terminal phone jack priority (if connected to phone jack, voice changes automatically) Input 2: -20 dB*, 10 KΩ, balanced, screw terminal
Remote Microphone	Usable remote microphone: RM-200M Max 4 unit, RJ45 Maximum Cable Distance: Total 800m
S/N Ratio	Over 60 dB
Total Harmonic Distortion	Under 1 % at 1 kHz, 1 /3 rated power
Frequency Response	50 Hz - 20000 Hz
Tone Control	Bass: ± 10 dB at 100 Hz Treble: ± 10 dB at 10 kHz