



0.00 SAR ✓ In Stock

FEATURES :

- Flat front panel
- Quick and easy installation
- Fire dome made of steel
- Snap in cable terminal
- 6 W rated input
- 12 cm speaker

+966 530651576 | www.unityservicesksa.com

TOA PC-1860F 6W Ceiling Mount Speaker

Rated Input	6 W (100 V line), 3 W (70 V line)
Rated Impedance	100 V line: 1.7 kΩ (6 W), 3.3 kΩ (3 W), 6.7 kΩ (1.5 W), 13 kΩ (0.8 W) 70 V line: 1.7 kΩ (3 W), 3.3 kΩ (1.5 W), 6.7 kΩ (0.8 W), 13 kΩ (0.4 W)
Sensitivity	95 dB (1 W, 1 m) (500 Hz - 5 kHz, pink noise)
Frequency Response	170 Hz - 20 kHz (peak -20 dB)
Speaker Component	12 cm (5") cone-type
Mounting Hole	Mounting hole: Ø156±3 mm (6.14±0.12") Ceiling thickness: 5 - 25 mm (0.2" - 0.98")
Cable Requirements	Solid wire: 0.5 - 3 mm ² (AWG 20 - 12)
Operating Temperature	-10 °C to +50 °C (14 °F to 122 °F)
Dimensions	Ø180 x 5 (exposed section) + 100 (D) mm (7.09 x 0.2" + 3.94")
Weight	1 kg (2.2 lb)