TOA PC-2360EN 6W Ceiling Speaker – EN54-24 Certified Voice Alarm & Fire Evacuation Speaker



0.00 SAR ✓ In Stock

FEATURES :

- Flat front panel
- Quick and easy installation
- Dripping-water protection
- Snap in cable terminal
- 6 W rated input
- 16 cm speaker chassis

TOA PC-2360EN 6W Ceiling Speaker	
Rated Input	6 W (100 V line), 3 W (70 V line)
Rated Impedance	100 V line: 1.7 kΩ (6 W), 3.3 kΩ (3 W), 6.7 kΩ (1.5 W), 13 kΩ (0.8 W) 70 V line: 1.7 kΩ (3 W), 3.3 kΩ (1.5 W), 6.7 kΩ (0.8 W), 13 kΩ (0.4 W)
Sensitivity	94 dB (1 W, 1 m) (500 Hz - 5 kHz, pink noise) 92 dB (1 W, 1 m) (100 Hz - 10 kHz, pink noise) 80 dB (1 W, 4 m) (100 Hz - 10 kHz, pink noise)
Max. Sound Pressure Level	99 dB (6 W, 1 m) (100 Hz - 10 kHz, pink noise) 87 dB (6 W, 4 m) (100 Hz - 10 kHz, pink noise)
Frequency Response	60 Hz - 20 kHz (peak -20 dB)
Coverage Angle (-6 dB)	Horizontal and Vertical: 160° (500 Hz), 170° (1 kHz), 160° (2 kHz), 60° (4 kHz) according to EN54-24
Speaker Component	16 cm (5") cone-type
Operating Temperature	-10 °C to + 50 °C (14 °F to 122 °F)
Dimensions for Fixing Hole	Mounting hole: φ200±3 mm (φ7.87"±0.12") Ceiling thickness: 5 - 25 mm (0.2" - 0.98")
Applicable Cable	Solid wire: 0.5 - 3 mm² (AWG 20 - 12)
Finish	Frame: Steel plate, white (RAL 9016 equivalent), paint Grille: Steel net, white (RAL 9016 equivalent), paint
Dimensions	φ230 × 76 (D) mm (φ9.06" × 2.99")
Weight	740 g (1.63 lb)