



0.00 SAR ✓ In Stock

FEATURES :

- Rated Input: 15 W (100 V, 70 V line)
- 70 V line: 330 Ω (15 W), 670 Ω (7.5 W), 1 k Ω (5 W), 2 k Ω (2.5 W), 3.3 k Ω (1.5 W)
- Sensitivity : 96 dB (1 W, 1 m) (500 Hz – 5 kHz, pink noise)

+966 530651576 | www.unityservicesksa.com

TOA PC-2852 15Watt Ceiling Speaker

Rated Input	15 W (100 V, 70 V line)
Rated Impedance	100 V line: 670 Ω (15 W), 1 k Ω (10 W), 2 k Ω (5 W), 3.3 k Ω (3 W)
Sensitivity :	96 dB (1 W, 1 m) (500 Hz – 5 kHz, pink noise)
Frequency Response	45 Hz – 20 kHz (peak -20 dB)
Dimensions for Fixing Hole	Mounting hole: $\phi 250 \pm 3$ mm ($\phi 9.84'' \pm 0.12''$)
Ceiling thickness:	5 – 25 mm (0.2" – 0.98")
Dimensions	$\phi 280 \times 92$ (D) mm ($\phi 11.02'' \times 3.62''$)
Weight	1.6 kg (3.53 lb)