TOA PC-2869 Ceiling Mount Speaker



0.00 SAR ✓ In Stock

FEATURES :

Integrated with a speaker unit and panel, the PC-2869 Ceiling Mount Speaker is of all metallic construction and ideal for use in a voice alarm system. It feature spring clamp mechanism for easy speaker mounting to the ceiling. The input impedance can be easily changed by changing the tap position of the transformer. The push-in type input terminal block makes cable connections easy and allows bridge wiring.

TOA PC-2869 Ceiling Mount Speaker	
Rated Input	6 W (100 V line), 3 W (70 V line)
Rated Impedance	100 V line: 1.7 kΩ (6 W), 3.3 kΩ (3 W), 6.7 kΩ (1.5 W), 13 kΩ (0.8 W) 70 V line: 1.7 kΩ (3 W), 3.3 kΩ (1.5 W), 6.7 kΩ (0.8 W), 13 kΩ (0.4 W)
Sensitivity	94 dB (1 W, 1 m) (500 Hz - 5 kHz, pink noise)
Frequency Response	40 Hz - 20 kHz (peak -20 dB)
Speaker Component	20 cm (8") double cone-type
Dimensions for Fixing Hole	Mounting hole: φ250±3 mm (φ9.84"±0.12") Ceiling thickness: 5 - 25 mm (0.2" - 0.98")
Applicable Cable	600 V vinyl-insulated cable (IV wire or HIV wire) Solid copper wire: φ0.8 - φ1.6 mm (equivalent to AWG 20 - 14) 7-core twisted copper wire: 0.75 - 1.25 m□ (equivalent to AWG 18 - 16)
Dimensions	φ280 × 92 (D) mm (φ11.02" × 3.62")
Weight	1.4 kg (3.09 lb)