TOA PC-648R 6-Watts 100V Ceiling Speaker High Quality



100.00 SAR ✓ In Stock

FEATURES :

Rated Power: 15-Watt
Impedance Option: 100V/70V
Sensivity: 96dB
Mounting Method: Spring clamp
Japan Origin, made Indonesia

Toa PC-668R 15-Watts Ceiling Mount Speaker

RATED INPUT	15 W (100 V, 70 V line)
IMPEDANCE OPTION	100 V line: 670 Ω (15 W), 1 kΩ (10 W), 2 kΩ (5 W), 3.3kΩ (3 W) 70 V line: 330 Ω (15 W), 670 Ω (7.5 W), 1 kΩ (5 W), 2 kΩ (2.5 W), 3.3 kΩ (1.5 W)
SENSITIVITY	96 dB (Pink Noise 500 Hz – 5,000 Hz / 1W, 1m)
FREQUENCY RESPONSE	65 Hz – 20,000 Hz (at 20 dB below peak SPL)
SPEAKER COMPONENT	20 cm (8″) double cone-type
DIMENSIONS FOR FIXING HOLE	Mounting hole: Φ250±5 mm (Φ9.84″±0.2″) Ceiling thickness: 5 – 25 mm (0.20″ – 1.98″)
FINISH	Panel: Polypropylene resin, traffic white (RAL 9016 equivalent) Grille: Surface-treated steel plate net, traffic white (RAL 9016 equivalent), paint
DIMENSIONS	Φ280 × 90 (D) mm (11.02″ × 3.54″)
WEIGHT	0.96 kg (2.12 lb)