



2,450.00 SAR ✓ In Stock

FEATURES :

Rated Power: 15-Watt

Impedance Option: 100V/70V

Sensitivity: 96dB

Mounting Method: Spring clamp

Japan Origin, made Indonesia

+966 530651576 | www.unityservicesksa.com

Toa PC-668R 15-Watts Ceiling Mount Speaker

RATED INPUT	15 W (100 V, 70 V line)
IMPEDANCE OPTION	100 V line: 670 Ω (15 W), 1 k Ω (10 W), 2 k Ω (5 W), 3.3k Ω (3 W) 70 V line: 330 Ω (15 W), 670 Ω (7.5 W), 1 k Ω (5 W), 2 k Ω (2.5 W), 3.3 k Ω (1.5 W)
SENSITIVITY	96 dB (Pink Noise 500 Hz – 5,000 Hz / 1W, 1m)
FREQUENCY RESPONSE	65 Hz – 20,000 Hz (at 20 dB below peak SPL)
SPEAKER COMPONENT	20 cm (8") double cone-type
DIMENSIONS FOR FIXING HOLE	Mounting hole: $\Phi 250 \pm 5$ mm ($\Phi 9.84" \pm 0.2"$) Ceiling thickness: 5 – 25 mm (0.20" – 1.98")
FINISH	Panel: Polypropylene resin, traffic white (RAL 9016 equivalent) Grille: Surface-treated steel plate net, traffic white (RAL 9016 equivalent), paint
DIMENSIONS	$\Phi 280 \times 90$ (D) mm (11.02" $\times$ 3.54")
WEIGHT	0.96 kg (2.12 lb)