TOA PC-648R Ceiling Speaker



0.00 SAR ✓ In Stock

FEATURES :

Integrated with a resin panel and speaker frame, the PC-648R is the ceiling mount speaker with a metal attached. It features spring clamp mechanism for easy speaker mounting to the ceiling. The input impedance can be easily changed by changing the tap position of the transformer.

TOA PC-648R Ceiling Speaker

RATED INPUT	6 W (100 V line), 3 W (70 V line)
RATED IMPEDANCE	100 V line: 1.7 kΩ (6 W), 3.3 kΩ (3 W), 10 kΩ (1 W) 70 V line: 1.7 kΩ (3 W), 3.3 kΩ (1.5 W), 10 kΩ (0.5 W)
SENSITIVITY	90 dB (1 W, 1 m) (500 Hz – 5 kHz, pink noise)
FREQUENCY RESPONSE	100 Hz – 18 kHz (peak -20 dB)
SPEAKER COMPONENT	12 cm (5″) cone-type
DIMENSIONS FOR FIXING HOLE	Mounting hole: φ145±5 mm (φ5.71″±0.2″) Ceiling thickness: 5 – 25 mm (0.2″ – 0.98″)
FINISH	Baffle: Polypropylene resin, white (RAL 9016 equivalent) Grille: Surface-treated steel plate net, white (RAL 9016 equivalent), paint
DIMENSIONS	φ168 × 77 (D) mm (φ6.61″ × 3.03″)
WEIGHT	470 g (1.04 lb)