# TOA PC-658R 6Watt Ceiling Speaker High Sound




**110.00 SAR** ✓ In Stock

**FEATURES :**

Integrated with a resin panel and speaker frame, the PC-658R is the ceiling mount speaker with a metal attached. It features spring clamp mechanism for easy speaker mounting to the ceiling. The input impedance can be easily changed by changing the tap position of the transformer.

| TOA PC-658R 6Watt Ceiling Speaker | |
|---|---|
| RATED INPUT | 6 W (100 V line), 3 W (70 V line) |
| RATED IMPEDANCE | 100 V line: 1.7 kΩ (6 W), 3.3 kΩ (3 W), 10 kΩ (1 W) 70 V line: 1.7 kΩ (3 W), 3.3 kΩ (1.5 W), 10 kΩ (0.5 W) |
| SENSITIVITY | 90 dB (1 W, 1 m) (500 Hz – 5 kHz, pink noise) |
| FREQUENCY RESPONSE | 65 Hz – 18 kHz (peak -20 dB) |
| SPEAKER COMPONENT | 16 cm (6″) cone-type |
| DIMENSIONS FOR FIXING HOLE | Mounting hole: φ170±5 mm (φ6.69″±0.2″) Ceiling thickness: 5 – 25 mm (0.2″ – 0.98″) |
| DIMENSIONS | φ192 × 73 (D) mm (φ7.56″ × 2.87″) |
| WEIGHT | 500 g (1.1 lb) |