



0.00 SAR ✓ In Stock

FEATURES :

Integrated with a resin panel and speaker frame, the PC 658R is the ceiling mount speaker with a metal attached. It features spring clamp mechanism for easy speaker mounting to the ceiling. The input impedance can be easily changed by changing the tap position of the transformer.

+966 530651576 | www.unityservicesksa.com

TOA PC-658R Ceiling Speaker

RATED INPUT	6 W (100 V line), 3 W (70 V line)
RATED IMPEDANCE	100 V line: 1.7 k Ω (6 W), 3.3 k Ω (3 W), 10 k Ω (1 W) 70 V line: 1.7 k Ω (3 W), 3.3 k Ω (1.5 W), 10 k Ω (0.5 W)
SENSITIVITY	90 dB (1 W, 1 m) (500 Hz – 5 kHz, pink noise)
FREQUENCY RESPONSE	65 Hz – 18 kHz (peak -20 dB)
SPEAKER COMPONENT	16 cm (6") cone-type
DIMENSIONS FOR FIXING HOLE	Mounting hole: $\phi 170 \pm 5$ mm ($\phi 6.69" \pm 0.2"$) Ceiling thickness: 5 – 25 mm (0.2" – 0.98")
FINISH	Baffle: Polypropylene resin, white (RAL 9016 equivalent) Grille: Surface-treated steel plate net, white (RAL 9016 equivalent), paint
DIMENSIONS	$\phi 192 \times 73$ (D) mm ($\phi 7.56" \times 2.87"$)
WEIGHT	500 g (1.1 lb)