



0.00 SAR ✓ In Stock

FEATURES :

- Type: Ceiling Mount Speaker
- Output Power: 30 W (Max)
- Impedance: 8 Ohms

+966 530651576 | www.unityservicesksa.com

TOA PC-668RC Ceiling Mount Speaker

Rated Input	15 W (100 V, 70 V line)
Impedance Option	100 V line: 670 Ω (15 W), 1 kΩ (10 W), 2 kΩ (5 W), 3.3kΩ (3 W) 70 V line: 330 Ω (15 W), 670 Ω (7.5 W), 1 kΩ (5 W), 2 kΩ (2.5 W), 3.3 kΩ (1.5 W)
Sensitivity	96 dB (Pink Noise 500 Hz - 5,000 Hz / 1W, 1m)
Frequency Response	65 Hz - 20,000 Hz (at 20 dB below peak SPL)
Speaker Component	20 cm (8") double cone-type
Dimensions for Fixing Hole	Mounting hole: $\Phi 250 \pm 5$ mm ($\Phi 9.84" \pm 0.2"$) Ceiling thickness: 5 - 25 mm (0.20" - 1.98")
Speaker Mounting Method	Spring clamp
Input Connector	Push-In Connector (Bridging and branch connection possible)
Finish	Panel: Polypropylene resin, traffic white (RAL 9016 equivalent) Grille: Surface-treated steel plate net, traffic white (RAL 9016 equivalent), paint
Dimensions	$\Phi 280 \times 90$ (D) mm (11.02" $\times$ 3.54")
Weight	0.97 kg (2.14 lb)