TOA RM-300MF Fireman's Mic – Professional Voice Alarm Interface – Dedicated Emergency Key & Zone Expansion



0.00 SAR ✓ In Stock

FEATURES :

The RM-300MF Fireman's Microphone is designed for exclusive use with the VM-3000 Series. It is equipped with an emergency activation key, permitting pre-recorded evacuation and alert announcements to be activated, and microphone announcement to be made in emergency situations. By connecting the RM-320F Fireman's Microphone Extension to the RM-300MF, the number of function keys can be expanded. The zone selection or failure acknowledgment function can be assigned to such function keys.

TOA RM-300MF Fireman's Microphone	
Power Source	24 V DC (operating range: 15 - 40 V DC, supplied from the VM-3000 system)
Current Consumption	120 mA (RM-300MF), 660 mA (with 3 RM-320F connected)
Frequency Response	200 Hz - 15 kHz
S/N Ratio	55 dB or more
Connection Cable	Main line: Shield CPEV cable (each one pair of Audio line, Data line, Power supply line) or Category 5 Shielded Twisted-Pair straight cable for LAN (CAT5-STP), M3 screw terminal
Maximum Cable Distance	Total 800 m (874.89 yd)
No. of Connectable RM-320F	Max. 3 units
Indicator	Power indicator, Emergency indicator, Communication failure indicator, CPU OFF indicator, Evacuation announcement indicator, Alert announcement indicator, Emergency reset indicator, Microphone in-use indicator, Emergency broadcast equipment in-use indicator
Operating Temperature	-5 ℃ to +45 ℃ (23 □F to 113 □F)
Operating Humidity	5 % to 95 %RH (no condensation)
Finish	ABS resin, blueish gray (PANTONE 538 or its equivalent)
Dimensions	200 (W) × 215 (H) × 82.5 (D) mm (7.87" × 8.46" × 3.25")
Weight	1.1 kg (2.43 lb) (with wall mounting bracket unit)
Accessory	Wall mounting bracket unit...1, Wall mounting screw...2