



0.00 SAR ✓ In Stock

FEATURES :

Dust/Water Protection: IP65
 Frequency Response: 200 Hz – 6,000 Hz
 Sound Pressure Level: 110 dB (1 W, 1 m)
 Operating Temperature: -20 °C to +55 °C
 Driver Coupling: 1 – 3/8 18 threads (inch screw)
 Applicable Drivers: TU-632, TU-632M, TU-652, TU-652M

+966 530651576 | www.unityservicesksa.com

TOA TH-652 Horn Speaker

APPLICABLE DRIVERS	TU-632, TU-632M, TU-652, TU-652M
SOUND PRESSURE LEVEL	110 dB (1 W, 1 m) (When operated with a driver.)
FREQUENCY RESPONSE	200 Hz – 6,000 Hz (When operated with a driver.)
DUST/WATER PROTECTION	IP65 (When operated with a driver.)
DRIVER COUPLING	1 – 3/8 18 threads (inch screw)
OPERATING TEMPERATURE	-20 °C to +55 °C (must be free from dew condensation)
FINISH	Horn flare and flange: Aluminum, White, powder coating Reflector horn: HIPS, White Bracket: Steel, White, powder coating Screws and bolts: Stainless steel
DIMENSIONS	Φ500 × 357 (D) mm
WEIGHT	2.7 kg