TOA TS-680 Central Unit for Conference System



3,400.00 SAR ✓ In Stock

FEATURES :

• Compatibility: Connects with TOA TS-681L chairman units and TS-682L delegate units.
• Capacity: Supports up to 24 conference units standard.
• Control: Features priority speech chimes and automatic mic-off settings (30 seconds or off).
• Rack Mounting: Fits standard EIA equipment racks using an optional bracket (MB-23B).

TOA TS-680 Central Unit for Conference System	
Power Source	220 - 240 V AC, 50/60 Hz
Power Consumption	20 W
Rated Output	36 V DC, 480 mA
Input	Selectable MIC or AUX Mic: -60dB*, 600 Ω, unbalanced, phone jack AUX: -20 dB*, 10 kΩ, unbalanced, phone jack
Output	Recording: -20dB*, 10 kΩ, unbalanced, RCA jack
Number of Connectable Units	Max. 24 units
Control	Priority speech chime: Operation of TS-681L's priority key activates a single-tone chime Speaker restriction: Number of simultaneously-usable TS-682L can be set up to 0-3 Automatic Mic-Off Function: OFF, 30s (selectable)
Operating Temperature	0 °C to +40 °C (32 °F to 104 °F)
Operating Humidity	90 %RH or less (no condensation)
Finish	Panel: Aluminum, black. 30% gloss, paint Case: Steel plate, black, 30% gloss, paint
Dimensions	420(W) x 96.1 (H) x 222.5(D) mm (16.54” x 3.78” x 8.76”)
Weight	2.7 kg (5.95 lb)
Accessory	Power Cord (2m) x 1
Option	Extension cord: YR-780-2M, YR-780-10M Rack mounting bracket: MB-23B