TOA TS-690 Central Unit – Reliable Conference System Controller



3,400.00 SAR ✓ In Stock

FEATURES :

- Digital signal processing
- 3 Central units can connect
- Priority speech chime
- Support 24 conference units
- Origin: Japan

TOA TS-690 Central Unit – Reliable Conference System Controller

Power Source	220 - 240 V AC, 50/60 Hz
Power Consumption	20 W
Rated Output	36 V DC, 480 mA
Input	Selectable MIC or AUX Mic: -60dB*, 600 Ω, unbalanced, phone jack AUX: -20 dB*, 10 kΩ, unbalanced, phone jack
Output	Recording: -20dB*, 10 kΩ, unbalanced, RCA jack
Number of Connectable Units Max.	24 units
Control	Priority speech chime: Operation of TS-691L priority button activates a single-tone chime Speaker restriction: Number of simultaneously-usable TS-692L can be set up to 0-3 Automatic Mic-Off Function: OFF, 30s (selectable)
Operating Temperature	0 °C to +40 °C (32 °F to 104 °F)
Operating Humidity	90 %RH or less (no condensation)
Finish	Panel: Aluminum, black. 30% gloss, paint Case: Steel plate, black, 30% gloss, paint
Dimensions	420(W) x 96.1 (H) x 222.5(D) mm (16.54” x 3.78” x 8.76”)
Weight	2.7 kg (5.95 lb)
Accessory	Power Cord (2m) x 1
Option	Extension cord: YR-790-3, YR-790-10 Rack mounting bracket: MB-23B