# Toa TS-691L Chairman Unit with Long Microphone




**1,050.00 SAR** ✓ In Stock

**FEATURES :**

- Chairman unit for Conference
- Priority to speak Button
- Built Light working status
- No noise touch switch design
- Built in Speaker

## Toa TS-691L Chairman Unit specification:

| | |
|---|---|
| POWER SOURCE | 36 V DC, 30 mA or less (supplied from the Central Unit TS-690) |
| OUTPUT | Headphone/Recording: Ø 3.5 mm, mini jack (3P: monaural) Internal speaker: 130 Ω, 200 mW |
| CONTROL | Speech: Microphone, speaker on-off control by speech button Priority: Microphone, speaker on-off, other microphone cut-off, and single-tone chime activation by priority button Volume control: Headphone/Recording and internal speaker volume adjustable |
| MICROPHONE UNIT (ACCESSORY) | Electret Condenser Microphone Directivity: Unidirectional Impedance: 1.8kΩ Sensitivity: -37dB (1kHz 0dB = 1V/Pa) Frequency Response: 100Hz – 13 kHz Length: 518mm Weight: 105g (0.23 lb) |
| OPERATING TEMPERATURE | 0 °C to +40 °C (32 °F to 104 °F) |
| OPERATING HUMIDITY | 90 %RH or less (no condensation) |
| DIMENSIONS | 145.3 (W) × 70.7 (H) × 150.5 (D) mm (5.72″ × 2.78″ × 5.93″) (Excluding Microphone Unit) |
| WEIGHT | 800 g (1.76 lb) (Excluding Microphone Unit) |
| ACCESSORY | Long Microphone Unit x 1 |
| OPTION | Extension cord: YR-790-3, YR-790-10 |