



0.00 SAR ✓ In Stock

FEATURES :

- Model: TS-7912D
- Power: 100-240V-AC,50/60Hz
- Rated Output: 120 W
- Units: Max. 64 units
- Weight: 4.9 kg

+966 530651576 | www.unityservicesksa.com

Toa TS-7912D Central Unit

Power Source	100 - 240 V AC, 50/60 Hz
Power / Current Consumption	230 W (rated output, 64 units) 81 W (1/8 of rated output, 64 units) 200 mA or less (when power switch is OFF)
Rated Output	120 W (Speaker Output)
Frequency Response	20 Hz to 20 kHz ± 3 dB
Distortion	1 % or less at 1 kHz (20 kHz LPF (AUX-0025))
Tone Control Bass:	± 10 dB at 100 Hz, Treble: ± 10 dB at 10 kHz (Speaker Out)
Signal to Noise Ratio	83 dB or more (Speaker volume: min.) 76 dB or more (Speaker volume: max, Input volume: min.) 55 dB or more (Speaker volume: max, Input volume: max.) (A-weighted)
Audio Input	Mic: -60dB* (unbalanced) / -41 dB* (balanced) selectable, 600 Ω , $\varnothing 6.3$ mm phone jack Note: MIC input is equipped with phantom power (24 V DC, ON/OFF switchable) AUX IN: -20 dB*, 10 k Ω , unbalanced, RCA pin jack x 2
Audio Output	SPEAKER OUT: High impedance (100 V line / total 83 Ω) / Low impedance (4 - 16 Ω) selectable, removable terminal block (3 pins) REC OUT: -10dB*, 10 k Ω , unbalanced, RCA pin jack x 2
Video Conference IN/OUT Terminal	-10dB*, 10 k Ω , unbalanced, RCA pin jack USB Audio Type-B port (for PC) Audio streaming data-in: 11.025/16/22.05/32/44.1/48 kHz sampling frequency (selectable on PC), 16-bit PCM. Audio streaming data-out: 32/44.1/48 kHz sampling frequency (selectable on PC), 16-bit PCM.
Chairman/Delegate Unit Terminal	LINE 1, 2: 8 pin DIN Socket
Dimensions	420(W) x 96.1 (H) x 313.1(D) mm
Operating Temperature	0 $^{\circ}$ C to +40 $^{\circ}$ C (32 $^{\circ}$ F to 104 $^{\circ}$ F)
Operating Humidity	90 %RH or less (no condensation)
Weight	4.9 kg

Accessory	Power Cord (2 m) x 1 USB Cable (3 m) x 1 Speaker out removable terminal plug (5 mm, 3 pins) x 1
Option	Extension cord: YR-790-3, YR-790-10 Rack mounting bracket: MB-25B