TOA TS-7912DW Central Unit – Powerhouse for Wired Conference Systems



6,000.00 SAR ✓ In Stock

FEATURES :

- Model: TS-7912DW
- Power: 100 – 240V
- Rated Output: 120 W
- Humidity: 90 %RH
- Weight: 5.2 kg

TOA TS-7912DW Central Unit – Powerhouse for Wired Conference Systems

Power Source	100 - 240 V AC, 50/60 Hz
Power / Current Consumption	235 W (rated output, 64 units) 85 W (1/8 of rated output, 64 units) 200 mA or less (when power switch is OFF)
Rated Output	120 W (Speaker Output)
Frequency Response	20 Hz to 20 kHz ±3 dB
Tone Control	Bass: ±10 dB at 100 Hz, Treble: ±10 dB at 10 kHz (Speaker Out)
Signal to Noise Ratio	83 dB or more (Speaker volume: min.) 76 dB or more (Speaker volume: max, Input volume: min.) 55 dB or more (Speaker volume: max, Input volume: max.) (A-weighted)
Audio Input	Mic: -60dB* (unbalanced) / -41 dB* (balanced) selectable, 600 Ω, Ø6.3 mm phone jack Note: MIC input is equipped with phantom power (24 V DC, ON/OFF switchable) AUX IN: -20 dB*, 10 kΩ, unbalanced, RCA pin jack x 2 MODULE 1, 2: -20 dB*, 10 kΩ, compatible Wireless Tuner Module WTU-M9800
Audio Output	SPEAKER OUT: High impedance (100 V line / total 83 Ω) / Low impedance (4 - 16 Ω) selectable, removable terminal block (3 pins) REC OUT: -10dB*, 10 kΩ, unbalanced, RCA pin jack x 2
Video Conference IN/OUT Terminal	-10dB*, 10 kΩ, unbalanced, RCA pin jack USB Audio Type-B port (for PC) Audio streaming data-in: 11.025/16/22.05/32/44.1/48 kHz sampling frequency (selectable on PC), 16-bit PCM. Audio streaming data-out: 32/44.1/48 kHz sampling frequency (selectable on PC), 16-bit PCM.
Chairman/Delegate Unit Terminal	LINE 1, 2: 8 pin DIN Socket
LED Indicators	Power (Green) Amplifier: INPUT SIGNAL (Green), PEAK (Red), PROTECT (Red), ERROR (Red) Conference Unit Setting: NORMAL (Green), AUTO MIC OFF (Green), TEST (Red)
Operating Temperature	0 °C to +40 °C (32 °F to 104 °F)
Operating Humidity	90 %RH or less (no condensation)
Dimensions	420(W) x 96.1 (H) x 313.1(D) mm
Weight	5.2 kg

Accessory	Power Cord (2 m) x 1 USB Cable (3 m) x 1 Speaker out removable terminal plug (5 mm, 3 pins) x 1