Toa TS-791L Chairman Unit Long Microphone Conference System



1,600.00 SAR ✓ In Stock

FEATURES :

- Model: TS-791L
- Power: 36 V DC, 30mA
- Sensitivity: -37 dB
- Frequency :100 Hz-13 kHz
- Temperature: 0 ℃ to+40 ℃

TOA TS-791L Chairman Unit Long Microphone Conference System

Power Source	36 V DC, 30 mA or less (supplied from the Central Unit TS-7912D, TS-7912DW)
Output	Headphone/Recording: Ø3.5 mm, mini jack (3P: monaural) × 2 Monitor speaker: 130 Ω, 200 mW
Control	Speech: Microphone, speaker on-off control by speech button Priority: Microphone, speaker on-off, other microphone cut off and single-tone chime activation by priority button Volume control: Headphone/Recording and monitor speaker volume adjustable x 2
Microphone Unit (Accessory)	Electret condenser microphone Directivity: Unidirectional Impedance: 1.8 kΩ Sensitivity: -37 dB (1 kHz 0 dB = 1 V/Pa) Frequency Response: 100 Hz - 13 kHz LED indicator: Speech indicator (ring type) Blue Length: 518 mm Weight: 105 g
Operating Temperature	0 ℃ to +40 ℃
Operating Humidity	90 %RH or less (no condensation)
Finish	Upper case: ABS resin, dark grey, paint Lower case: ABS resin, black, paint
Dimensions	145.3 (W) × 70.7 (H) × 150.5 (D) mm (Excluding microphone unit)
Weight	800 g
Accessory	Long microphone unit x 1
Option	Extension cord: YR-790-3, YR-790-10