TOA TU-651M Driver Unit



0.00 SAR ✓ In Stock

FEATURES :

High-impedance (70 V / 100 V lines) model
Power rating: 50 W
Frequency Response: 150 Hz – 6 kHz
Input impedance selector on high-impedance models facilitates input impedance matching from the outside
IP65 certified weatherproof construction

TOA TU-651M Driver Unit	
RATED INPUT	50 W
RATED IMPEDANCE	16 Ω
SENSITIVITY	110 dB (1 W, 1 m) (When operated with JIS C 5504 standard horn.)
FREQUENCY RESPONSE	150 Hz – 6 kHz (When operated with JIS C 5504 standard horn.)
DUST/WATER PROTECTION	IP65 (When a driver is operated with a horn.)
HORN COUPLING	1 – 3/8 18 threads (inch screw)
POLARITY	Hot: Black, Com: White
OPERATING TEMPERATURE	-20 %%dC to +55 %%dC (-4 □F to +131 □F) (no condensation)
FINISH	Flange: Aluminum, gray, powder coating Rear cover: ABS resin, gray Screws: Stainless steel Speaker cable: Polyvinyl chloride insulated cabtyre cable (6 mm (0.24″) in diameter, 600 mm (23.62″) in length)
DIMENSIONS	%c139 × 106 (D) mm (φ5.47″ × 4.17″)
WEIGHT	2 kg (4.41 lb)