



0.00 SAR ✓ In Stock

FEATURES

The TU-652M is a highly intelligible driver unit suited to public address announcement applications. The driver unit is used in combination with a suitable horn (optional). Powder-coated finish and stainless steel screws ensure the unit's weatherproof capability.

+966 530651576 | www.unityservicesksa.com

TOA TU-652M Driver Unit

APPLICABLE HORNS	TU-652M
RATED INPUT	50 W
LINE VOLTAGE	100 V line or 70 V line
RATED IMPEDANCE	100 V line: 200 Ω (50 W), 330 Ω (30 W), 670 Ω (15 W) 70 V line: 100 Ω (50 W), 200 Ω (25 W), 330 Ω (15 W), 670 Ω (7.5 W)
OUTPUT SOUND PRESSURE LEVEL	110 dB (1 W, 1 m) (When operated with JIS C 5504 standard horn.)
FREQUENCY RESPONSE	150 Hz – 6,000 Hz (When operated with JIS C 5504 standard horn.)
HORN COUPLING	1 – 3/8 18 threads (inch screw)
OPERATING TEMPERATURE	-20°C to +55°C (-4°F to +131°F) (must be free from dew condensation)
FINISH	Upper Cover: Aluminum, White, powder coating Unit Case: HIPS. White Screws: Stainless steel Speaker cable: Polyvinyl chloride insulated cabtyre cable (6 mm (0.24") in diameter, 450 mm (17.72") in length), White
DIMENSIONS	$\Phi 139 \times 149$ (D) mm ($\Phi 5.47" \times 5.87"$)
WEIGHT	2.7 kg (5.95 lb)