



0.00 SAR ✓ In Stock

FEATURES :

Model: TU-660M

Applicable Horns: TH-650, TH-660

Rated Input: 60 W

Rated Impedance: 16 Ω

Sensitivity: 110 dB (1 W, 1 m) (When operated with JIS C 5504 standard horn.)

Frequency Response: 150 Hz – 8 kHz (When operated with JIS C 5504 standard horn.)



+966 530651576



www.unityservicesksa.com

TOA TU-660M Driver Unit 60W

Model:	TU-660M
Applicable Horns:	TH-650, TH-660
Rated Input:	60 W
Sensitivity:	110 dB (1 W, 1 m) (When operated with JIS C 5504 standard horn.)
Frequency Response:	150 Hz – 8 kHz (When operated with JIS C 5504 standard horn.)
Horn Coupling:	1 – 3/8 18 threads (inch screw)
Operating Temperature:	-20 °C to 55 °C (-4 °F to 131 °F) (no condensation)
Finish: Flange-: Aluminum, gray, powder coating; Rear cover-: ABS resin, gray; Screws-: Stainless steel; Speaker cable-: Polyvinyl chloride insulated capture cable (6 mm (0.24") in diameter, 600 mm (23.62") in length)	Flange-: Aluminum, gray, powder coating; Rear cover-: ABS resin, gray; Screws-: Stainless steel; Speaker cable-: Polyvinyl chloride insulated capture cable (6 mm (0.24") in diameter, 600 mm (23.62") in length)
Dimensions:	139 × 109 (D) mm (5.47" × 4.29")
Weight:	2 kg (4.41 lb)