TOA TZ-206 20Watts Column Speaker System



0.00 SAR ✓ In Stock

FEATURES :

- Ball Proof Tested
- 90dB Sensitivity
- Push-In Terminal
- Aluminum Die-Cast
- 135 x 250 x 128mm dimension
- 1.9Kg Weight

TOA TZ-206 20W Column Speaker

RATED INPUT	20 W
RATED IMPEDANCE	100 V line: 500 Ω (20 W), 1 kΩ (10 W), 2 kΩ (5 W), 4 kΩ (2.5 W) 70 V line: 500 Ω (10 W), 1 kΩ (5 W), 2 kΩ (2.5 W), 4 kΩ (1.3 W)
SENSITIVITY	90 dB (1 W, 1 m)
FREQUENCY RESPONSE	150 Hz – 16,000 Hz
SPEAKER COMPONENT	10 cm cone-type × 2
FINISH	Enclosure: HIPS, black, paint Punched Net: Surface-tread steel plate, black, paint Speaker Bracket: Aluminum die-cast, black, paint Joint Bracket, Wall Bracket: Steel plate, t1.6, black, paint
ACCESSORY	Speaker Bracket x 1, Joint Bracket x 1, Wall Bracket x 1, Fixing Bolt (M5 x 60) x 1, Hexagon Bolt (M6 x 12) (with plain washer and spring washer) x 2, Machine Screw (M5 x 20) (with plain washer and spring washer) x 2, Hexagon Bolt (M8x 15) x 1
DIMENSIONS	135 (W) × 250 (H) × 128 (D) mm
WEIGHT	1.9 kg (unit only)