



0.00 SAR ✓ In Stock

FEATURES :

- 60-Watt
- Flexibility in installation
- Impedance matching
- Easy connection
- Ball proof tested

+966 530651576 | www.unityservicesksa.com

TOA TZ-606B Column Speaker System

Rated Input	60 W
Rated Impedance	100 V line: 170 Ω (60 W), 330 Ω (30 W), 670 Ω (15 W), 1.3 k Ω (7.5 W) 70 V line: 170 Ω (30 W), 330 Ω (15 W), 670 Ω (7.5 W), 1.3 k Ω (3.8 W)
Sensitivity	95 dB (1 W, 1 m)
Frequency Response	150 Hz - 16,000 Hz
Speaker Component	10 cm cone-type $\times$ 6
Finish	Enclosure: HIPS, black, paint Punched Net: Surface-tread steel plate, black, paint Speaker Bracket: Aluminum die-cast, black, paint Joint Bracket, Wall Bracket: Steel plate, t1.6, black, paint
Dimensions	135 (W) $\times$ 746 (H) $\times$ 128 (D) mm
Weight	5.5 kg (unit only)
Accessory	Speaker Bracket $\times$ 1, Joint Bracket $\times$ 1, Wall Bracket $\times$ 1, Fixing Bolt (M5 $\times$ 60) $\times$ 1, Hexagon Bolt (M6 $\times$ 12) (with plain washer and spring washer) $\times$ 2, Machine Screw (M5 $\times$ 20) (with plain washer and spring washer) $\times$ 2, Hexagon Bolt (M8 $\times$ 15) $\times$ 1
Option	Speaker Stand: ST-16A