



0.00 SAR ✓ In Stock

FEATURES :

Featuring slim construction, the TZ-S240W is a 2-way array speaker containing 22 speaker elements. The sound source speaker elements are vertically arranged in close proximity to each other and form a continuous linear sound source, achieving uniform sound pressure with less attenuation due to distance.

+966 530651576 | www.unityservicesksa.com

TOA TZ-S240W Slim Array Speaker

Enclosure	Bass Reflex Type
Max. Input Power	Continuous : 240 W Program : 480 W
Rated Impedance	8 Ω
Sensitivity	94 dB (1 W, 1 m)
Frequency Response	95 Hz - 20,000 Hz
Crossover Frequency	2,500 Hz
Speaker Component	Low Frequency : 10 cm (4") cone-type woofer x 8 High Frequency : 2.5 cm (1") Balanced Dome Tweeter x 24
Operating Temperature	-10 °C - +50 °C
Finish	Enclosure: White Painted MDF Board Grille: White Painted SPCC Punched Net
Dimensions	160 (W) × 950 (H) × 262 (D) mm
Weight	17 kg
Accessories	Mounting Bracket x 2
Option	Flying Bracket: SR-FB4 Wall Tilt Bracket: SR-TB4 Extension Plate: SR-EP4 Wall Mounting Bracket: SR-WB4 Stand Adaptor: SR-SA4 Floor Stand: SR-FS4 Matching Transformer: MT-S0601 (For high impedance)