TOA VM-3360E Digital Extension Unit – 360W Rated Output



0.00 SAR ✓ In Stock

FEATURES :

Model: VM-3360E
Power Source : 230 V AC, 50/60 Hz
Operating Humidity : 5 % to 95 %RH
Dimensions : 482 (W) × 132.6 (H) × 407 (D) mm
Weight: 19 kg (41.89 lb)

TOA VM-3360E Digital Extension Unit	
Power Source	230 V AC, 50/60 Hz
Power Consumption	850 W (with rated output signal), 380 W (according to EN62368-1)
Rated Output	360 W
Frequency Response	50 Hz - 20 kHz, ±3 dB (at 1/3 rated output)
Distortion	0.7 % or less (at rated output, 1 kHz)
S/N Ratio	85 dB or more
Input	External amplifier input: 100 V line, removable terminal block (14 pins)
Output	Speaker output 1 - 2: Max. (360 W) per output Speaker output 3 - 6: Max. (120 W) per output Speaker output 1 - 6: Total within 360 W, removable terminal block (14 pins) Allowable minimum load: 500 Ω (20 W) at 100 V line for speaker line failure detection Direct output: Direct output from internal or external amplifier, removable terminal block (16 pins)
Power Input/Output	Power in: Connecting the VX-2000DS only (operating range: 20 - 40 V DC) PS out: 28 V DC/24 A M4 screw terminal, distance between barriers: 11 mm (0.43")
Operating Temperature	-5 °C to +45 °C (23 □F to 113 □F)
Operating Humidity	5 % to 95 %RH (no condensation)
Dimensions	482 (W) × 132.6 (H) × 407 (D) mm (18.98" × 5.22" × 16.02")
Weight	19 kg (41.89 lb)