TOA VP-2064 4-Channel Power Amplifier – 60W x 4 High-Impedance Amp



0.00 SAR ✓ In Stock

FEATURES :

The VP-2064 Power Amplifier features a 60 W by-4 channels configuration, and uses the VP-200VX Power Amplifier Module per channel.

TOA VP-2064 4-Channel Power Amplifier

Power Source	28 V DC (operating range: 20 - 40 V DC) M4 screw terminal, distance between barriers: 12 mm
Current Consumption	4.8 A in total (EN60065)
Rated Output Power	60 W × 4 (at min. resistive and max. capasitive load)
Output Power (at AC Mains: 195.5 V)	45 W × 4 (at min. resistive and max. capasitive load)
Output Voltage	100 V (70 V, 50 V: selectable by internal wiring change)
Frequency Response	40 Hz - 16 kHz, ±3 dB (at 1/3 rated output)
Distortion	1 % or less (at rated output, 1 kHz)
S/N Ratio	80 dB or more
Operating Temperature	0 ℃ to +40 ℃
Finish	Panel: Surface-treated steel plate, black, 30 % gloss, paint
Dimensions	482 (W) × 88.4 (H) × 345 (D) mm
Weight	11.2 kg
Accessory	Rack mounting screw…4, Fiber washer…4