



0.00 SAR ✓ In Stock

FEATURES :

The VP-2241 Power Amplifier features a 240 W-by-1 channels configuration, and uses the VP-200VX Power Amplifier Module per channel.

+966 530651576 | www.unityservicesksa.com

TOA VP-2241 240W Power Amplifier

Power Source	28 V DC (operating range: 20 - 40 V DC) M4 screw terminal, distance between barriers: 12 mm
Current Consumption	4.8 A (EN60065)
Rated Output Power	240 W (at min. resistive and max. capacitive load)
Output Power (at AC Mains: 195.5 V)	180 W (at min. resistive and max. capacitive load)
Output Voltage	100 V (70 V, 50 V: selectable by internal wiring change)
Minimum Resistive Load	41 Ω (at 100 V), 21 Ω (at 70 V), 10 Ω (at 50 V)
Maximum Capacitive Load	0.5 μ F (at 100 V), 1 μ F (at 70 V), 1 μ F (at 50 V)
Frequency Response	40 Hz - 16 kHz, ± 3 dB (at 1/3 rated output)
S/N Ratio	80 dB or more
Operating Temperature	0 $^{\circ}$ C to +40 $^{\circ}$ C
Dimensions	482 (W) $\times$ 88.4 (H) $\times$ 345 (D) mm
Weight	8.1 kg